

WBI

THE RADIANT PANEL COMPANY



**ecowarm® OSB
RADIANTBOARD™**

PREMIUM QUALITY RADIANT PANELS

Substrate: OSB from the makers of AdvanTech®

Nominal Dimensions: 23.5" x 47"

Thickness: 3/4"

Surface: 0.10 Aluminum Laminate

Groove Depth: 5/8"

PEX: 1/2" Nominal ASTM F 876-877 PEX

Groove Distance: 11.75" OC

Weight: 2.67 LBS / SQFT 20.5 LBS / Board

Pallet Size: 4'x4'x4' Full.

Pallet Capacity: 74 per Pallet

Packaging: Corner Protected. Shrink Wrapped.

Pallet Weight: 1,517 LBS

ECOWARM® RADIANTBOARD™ OSB SPECS



Ecowarm Radiantboard OSB is constructed using premium OSB substrate from the makers of *AdvanTech® with a laminated aluminum surface. Panels are designed for application over subfloor or concrete. Our patented U-shaped groove locks PEX tubing into place without the need for screws or staples. The channel creates the pathway into which 1/2" PEX tubing is placed. Our system can be used under almost any finished floor covering.

We've been manufacturing our patented radiant heating panels since 2000. The Ecowarm system is lightweight, fast responding, easy to install, and operates at a low water temperature resulting in high efficiency and lower operating costs.

*AdvanTech® is a registered trademark of Huber Engineered Woods LLC. Use of the AdvanTech® brand to describe the OSB substrate does not imply affiliation, sponsorship, or endorsement.

ECOWARM OSB PART NUMBERS

STRAIGHT: EWP-ECO-S2-OSB

END COMBO: EWP-ECO-C2-OSB

(877) 924-3899

wbiwarm.com